Package: mixediffusion (via r-universe)

October 7, 2026

Type Package

Title Mixed-Effects Diffusion Models with General Drift

Description Provides tools for likelihood-based inference in one-dimensional stochastic differential equations with mixed effects using expectation–maximization (EM) algorithms. The package supports Wiener and Ornstein–Uhlenbeck diffusion processes with user-specified drift functions, allowing flexible parametric forms including polynomial, exponential, and trigonometric structures. Estimation is performed via Markov chain Monte Carlo EM.

Version 1.0.1

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.3

Imports dplyr, adaptMCMC

Maintainer Pedro Abraham Montoya Calzada

<pedroabraham.montoya@gmail.com>

Depends R (>= 4.5)

LazyData true

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Pedro Abraham Montoya Calzada [aut, cre, cph] (ORCID: <https://orcid.org/0009-0002-3497-210X>), Rogelio Salinas Gutiérrez [aut, cph] (ORCID: <https://orcid.org/0000-0002-1669-4460>), Silvia Rodríguez-Narciso [aut, cph] (ORCID: <https://orcid.org/0000-0001-5429-5914>), Netzahualcóyotl Castañeda-Leyva [aut, cph] (ORCID: <https://orcid.org/0000-0001-9414-3923>)

Repository https://abraham1011.r-universe.dev

Date/Publication 2026-04-10 08:03:18 UTC

RemoteUrl https://github.com/cran/mixediffusion

RemoteRef HEAD

RemoteSha 7510f2904153f6f7789b953f5955430e8183b912

Contents

datasim01 2
datasim02 3
datasim03 4
fit_ou 5
fit_wiener 7
plot_paths 9

Index **10**

`datasim01` *Simulated diffusion dataset 01*

Description

A simulated dataset consisting of discretely observed trajectories generated from a one-dimensional Wiener diffusion model with random effects in the drift term.

Usage

```
data(datasim01)
```

Format

A data frame with observations from multiple experimental units and the following variables:

`t` Observation time.

`unit` Unit identifier.

`Y` Observed process value.

Details

The data were generated from the stochastic differential equation

$$dY_k(t) = a_k\, t\, dt + \sigma\, dW_k(t),$$

where the unit-specific random effects follow a normal distribution

$$a_k \sim \mathcal{N}(10, 3),$$

and the diffusion variance is given by $\sigma^2 = 500$.

The process was simulated for $K = 50$ units, each observed at $n = 200$ equally spaced time points, with initial condition $Y_{k0} = 1$.

Value

A data frame with simulated data.

Source

Simulated data generated for illustrative purposes.

References

None.

Examples

```
data(datasim01)
plot_paths(df = datasim01)
```

`datasim02` *Simulated diffusion dataset 02*

Description

A simulated dataset consisting of discretely observed trajectories generated from a one-dimensional Wiener diffusion model with random effects in the drift term.

Usage

```
data(datasim02)
```

Format

A data frame with observations from multiple experimental units and the following variables:

`t` Observation time.

`unit` Unit identifier.

`Y` Observed process value.

Details

The data were generated from the stochastic differential equation

$$dY_k(t) = a_k \sin(\pi t)\, dt + \sigma\, dW_k(t),$$

where the unit-specific random effects follow a normal distribution

$$a_k \sim \mathcal{N}(10, 3),$$

and the diffusion variance is given by $\sigma^2 = 50$.

The integrated drift used for simulation is given by

$$\mu_\Delta(a_k, t_i, t_{i-1}) = \frac{a_k}{\pi} \left\{ \cos(\pi t_{i-1}) - \cos(\pi t_i) \right\}.$$

The process was simulated for $K = 50$ units, each observed at $n = 200$ equally spaced time points, with initial condition $Y_{k0} = 1$.

Value

A data frame with simulated data.

Source

Simulated data generated for illustrative purposes.

References

None.

Examples

```
data(datasim02)
plot_paths(df = datasim02)
```

`datasim03` *Simulated diffusion dataset 03*

Description

A simulated dataset consisting of discretely observed trajectories generated from a one-dimensional Ornstein–Uhlenbeck diffusion model with a time-dependent mean function and random effects.

Usage

```
data(datasim03)
```

Format

A data frame with observations from multiple experimental units and the following variables:

`t` Observation time.

`unit` Unit identifier.

`Y` Observed process value.

Details

The data were generated from the stochastic differential equation

$$dY_k(t) = \lambda\{a_k t - Y_k(t)\}\, dt + \sigma\, dW_k(t),$$

where the unit-specific random effects follow a normal distribution

$$a_k \sim \mathcal{N}(10, 3),$$

the mean-reversion parameter is given by $\lambda = 0.75$, and the diffusion variance satisfies $\sigma^2 = 500$.

The process was simulated for $K = 30$ units, each observed at $n = 200$ equally spaced time points over the interval $[0, 10]$, with initial condition $Y_k(0) = 0$.

Value

A data frame with simulated data.

Source

Simulated data generated for illustrative purposes.

References

None.

Examples

```
data(datasim03)
plot_paths(df = datasim03)
```

---

fit_ou *Inference about the parameters of an Ornstein–Uhlenbeck process*

Description

Implements the EM algorithm to perform inference on the parameters of an Ornstein–Uhlenbeck process with mixed drift effects.

Usage

```
fit_ou(df,
  mu = "at^1",
  tol = 1e-4,
  max_iter = 100,
  theta = NULL,
  M = 100,
  verbose = TRUE,
  mu_cond = NULL,
  n_mcmc = 1000,
  burnin = 500)
```

Arguments

df	Data frame with the observed data. It must include the columns t (time), unit (unit identifier) and Y (the observed trajectory).
mu	Functional form of the drift. Supported drifts include "at^p", "exp(at)", "cos(at)" and "sin(at)". The default is "at^1".
tol	Convergence tolerance for the EM algorithm. The algorithm stops when the maximum absolute difference between the parameter estimates at two consecutive EM iterations is smaller than tol.
max_iter	Maximum number of EM iterations.
theta	Optional named vector of initial parameter values. If NULL, default initial values are used.
M	Number of Monte Carlo samples used to approximate the conditional expectations in the E-step.
verbose	Logical indicating whether to print EM iteration progress.
mu_cond	Optional user-supplied function defining the conditional mean of the process. If NULL, it is constructed automatically from mu.
n_mcmc	Number of MCMC iterations used in the E-step to sample the random effects.
burnin	Number of initial MCMC iterations discarded.

Details

The model is a one-dimensional Ornstein–Uhlenbeck diffusion defined by

$$dY_{kt} = \lambda\{\mu(t, a_k) - Y_{kt}\}\, dt + \sigma\, dW_{kt},$$

where $\mu(t, a_k)$ is a user-specified drift function depending on a unit-specific random effect $a_k \sim \mathcal{N}(\mu_a, \sigma_a^2)$.

The parameter λ controls the strength of mean reversion toward the time-dependent mean.

For discretely observed trajectories, the conditional mean is given by

$$E\{Y_{kt_i} \mid Y_{kt_{i-1}}, a_k\} = Y_{kt_{i-1}} e^{-\lambda \Delta t_i} + \lambda \int_{t_{i-1}}^{t_i} e^{-\lambda(t_i - s)} \mu(s, a_k)\, ds.$$

The function mu_cond represents this conditional mean. If not provided, it is constructed automatically from the drift specification supplied through mu using closed-form expressions.

Value

A named numeric vector containing the estimated model parameters:

mu_a	Estimated mean of the random effects distribution.
sigma2_a	Estimated variance of the random effects distribution.
sigma2	Estimated diffusion variance of the process.
lambda	Estimated mean reversion parameter.

Examples

```
library(mixediffusion)
data(datasim03)
plot_paths(df = datasim03)
fit <- fit_ou(df = datasim03, mu = "at^1",
              verbose = FALSE, max_iter = 1)
fit
```

`fit_wiener` *Inference about the parameters of a Wiener process*

Description

Implement the EM algorithm to perform inference on the parameters of a Wiener process with mixed drift effects.

Usage

```
fit_wiener(df,
  mu = "at^1",
  tol = 1e-4,
  max_iter = 100,
  theta = NULL,
  M = 100,
  verbose = TRUE,
  mu_dlt = NULL,
  n_mcmc = 1000,
  burnin = 500)
```

Arguments

`df`	Data frame with the observed data. It must include the columns `t` (time), `unit` (unit identifier) and `Y` (the observed trajectory).
`mu`	Functional form of the drift. Supported drifts include `"at^p"`, `"exp(at)"`, `"cos(at)"` and `"sin(at)"`. The default is `"at^1"`.
`tol`	Convergence tolerance for the EM algorithm. The algorithm stops when the maximum absolute difference between the parameter estimates at two consecutive EM iterations is smaller than `tol`.
`max_iter`	Maximum number of EM iterations.
`theta`	Optional named vector of initial parameter values. If `NULL`, default initial values are used.
`M`	Number of Monte Carlo samples used to approximate the conditional expectations in the E-step.
`verbose`	Logical indicating whether to print EM iteration progress.

mu_dlt	Optional user-supplied function defining the integrated drift term. If NULL, it is constructed automatically from mu.
n_mcmc	Number of MCMC iterations used in the E-step to sample the random effects.
burnin	Number of initial MCMC iterations discarded.

Details

The model is a one-dimensional Wiener diffusion defined by

$$dY_{kt} = \mu(t, a_k)dt + \sigma dW_{kt}$$

,

where $\mu(t, a_k)$ is a user-specified drift function depending on a unit-specific random effect $a_k \sim \mathcal{N}(\mu_a, \sigma_a^2)$.

For discretely observed trajectories, the mean of the increments is given by the integrated drift

$$\mu_\Delta(a_k, t_i, t_{i-1}) = \int_{t_{i-1}}^{t_i} \mu(s, a_k)\, ds.$$

The function mu_dlt represents this integrated drift. If not provided, it is constructed automatically from mu using closed-form expressions for common drift specifications.

Value

A named numeric vector containing the estimated model parameters:

mu_a	Estimated mean of the random effects distribution.
sigma2_a	Estimated variance of the random effects distribution.
sigma2	Estimated diffusion variance of the Wiener process.

Examples

```
library(mixediffusion)
data(datasim01)
plot_paths(df = datasim01)
fit <- fit_wiener(df = datasim01, mu = "at^1",
                  verbose = FALSE, max_iter = 1)
fit

# mu(ak,t) = ak*sin(pi*t)
data(datasim02)
plot_paths(df = datasim02)
mu_dlt_new <- function(ak,ti,ti_1){
  value <- -ak*(cos(pi*ti) - cos(pi*ti_1))
  return(value)
}

fit <- fit_wiener(df = datasim02, mu_dlt = mu_dlt_new,
                  verbose = FALSE, max_iter = 1)
fit
```

`plot_paths` *Plot panel trajectories*

Description

Plots multiple trajectories from panel or longitudinal data grouped by unit.

Usage

```
plot_paths(df,
  col = NULL,
  lwd = 1,
  xlab = "t",
  ylab = "Y",
  main = NULL,
  ...)
```

Arguments

`df`	Data frame containing the observed data. It must include the columns `t` (time), `unit` (unit identifier) and `Y` (observed values).
`col`	Optional vector of colors, one per unit. If `NULL`, a grayscale palette is used.
`lwd`	Line width used for the trajectories.
`xlab`	Label for the x-axis.
`ylab`	Label for the y-axis.
`main`	Optional main title for the plot.
`...`	Additional graphical parameters passed to `plot`.

Value

A ggplot graph.

Examples

```
data(datasim02)
plot_paths(datasim02)
```

Index

∗ **datasets**
    datasim01, 2
    datasim02, 3
    datasim03, 4

datasim01, 2
datasim02, 3
datasim03, 4

fit_ou, 5
fit_wiener, 7

plot_paths, 9